



CMX 36CH Recorder



Features

- LILIN IP cameras, fast domes, and DVRs/NVRs are supported.
- Up to 36 channels 1080P/3M/5M/8M network streaming, recording, and display
- 2U 19" chassis, built-in software RAID system, support up to 8 x 3.5" hot-swap HDDs.
- Failover, video archive, and SmartSearch support.
- Dual streamings decoding mode supported
- Dual monitors support, up to 36 channels video display.
- Support multi-channels playback for remote or local.
- Built-in dual port Gigabit Ethernet.

Description

LILIN CMX1036 36-channel recorder supports LILIN IP cameras, fast domes, and DVRs/NVRs. Up to 36 channels 1080p/3M/5M/8M network streaming, recording, and display. 2U 19" chassis, built-in software RAID system, support up to 8 x 3.5" hot-swap HDDs. Failover, video archive, and SmartSearch support. Dual streaming decoding mode supported.

Dual monitors support, up to 36 channels video display. Support multi-channels playback for remote or

local. Built-in dual port Gigabit Ethernet. Recording resolutions are 3840 x 2160, 2592 x 1944, 2048 x 1536, 1920 x 1080, 1280 x 1024, etc. CMX1036 supports audio recording, circular recording, limited recording, video archiving, low bitrate recording, and remote network RAID.
