



NAV 36CH Recorder



Caratteristica

- ONVIF Profile S, LILIN IP cameras, PTZ domes, DVRs, and NVRs supported
- Up to 36-ch 1080P/3M/4M/5M/8M network streaming, recording, and display
- Support 3.5"HDD x 3
- Failover, video archive, and Smart Search supported
- Dual streaming decoding mode supported
- Dual monitors supported, up to 36-ch video display
- Support multi-channels playback for remote or local NAV
- Support image archiving mechanisms
- Built-in dual port Gigabit Ethernet
- Provide up to 500Mbps upload and 500Mbps download network speed

File Descrizione

LILIN NAV2036A 36-ch Recorder supports LILIN IP cameras, PTZ dome IP cameras, DVRs, and NVRs. The recorder features up to 36-ch 1080P/3M/4M/5M/8M network streaming, recording, and display.

It is built-in dual port Gigabit Ethernet, and dual monitors. It also supports multi-channels playback for

remote or local NAV. Failover, video archive, and video sync are supported.

NAV2036A is capable of supporting continuous and schedule recordings. Various alarm detections include motion, alarm, audio, IVS, and ANPR (optional) for triggering various alarm outputs. NAV2036A also support up to 1080P 120FPS and 4K 30FPS video streams.

Simultaneous playback for 36-ch, dual monitors support, camera groupings, authentication, two-way audio, and dual-streaming provide extra flexibilities for the video management system.
