




PIH 402

- ⊕ Built-in High Definition Varifocal Lens
- ⊕ Integrated Dust Proof Design
- ⊕ Removable Lens Cap
- ⊕ Built-in Highly Sensitive Capacitive Microphone

Dimension Unit:mm



Audio Output



BLC



AGC



AWB



Vari-Focal

Specifications

⊕ Box type Camera

Name	Integrated Varifocal Camera		
Series Number	PIH-402		
Type	Standard Resolution		
Model	NTSC	PIH-4026N	PIH-4028N
	PAL	PIH-4026P	PIH-4028P
Lens	Focal Length	3 ~ 9mm	
	Iris	F1.4	
	Angle of View	H: 31.8° ~90.2° ; V:23.9° ~66.3° ; D:39.7° ~115.3°	
Power Supply	AC	24V ±10%	AC 90V~260V max.
	DC	12V ±10%	-
Image Pick-up Device	Sony 1/3" Super HAD CCD Sensor		
Effective Pixels	NTSC	510 (H) x 492 (V)	
	PAL	500 (H) x 582 (V)	
Chip size	5.59mm(H) x 4.68mm(V)		
H/V Sync. Frequency	NTSC	15.734KHz / 59.94Hz	
	PAL	15.625KHz / 50Hz	
Sync. Mode	Internal		
Resolution	380TV Lines		
Minimum Illumination	0.1 Lux / F1.4		
S/N Ratio	More than 50dB(AGC Off)		
Auto Gain Control	36dB Variable Gain		
White Balance	ATW		
Aperture Gain Correction	Horizontal , Vertical		
Scanning System	2:1 Interlace		
Back Light Compensation	Auto		
Video Output	CVBS 1.0Vpp / 75Ω BNC		
Audio Output	Yes		
Gamma Characteristic	γ =0.45		
Power Consumption	AC	24V / 2.5W	4.3W
	DC	12V / 3.0W	-
Operating Temperature	-10°C ~ + 50°C (14°F G42 ~122°F)		
Dimension	52mm (W) x 55mm (H) x 124mm(D)		
Weight	400g		