

NCS 36CH Control Server

NCS3600

www.meritlilin.com



HDMI



DisplayPort



H.264 / H.265



SSD



1080P

Introduction

LILIN NCS3600 36-channel Central Management System, supports all series of LILIN product such as LILIN IP cameras, PTZ dome IP cameras, Fisheye cameras, DVRs and NVRs. This can support up to 108 channels of 1080P/3MP/4MP/5MP/8MP/12MP resolution for live display.

It can support up to 3 of 3.5 inch Hard disks (Non-RAID) . One monitor can support up to 36 division view(480P 15fps) at the same time. The multi-channel playback is also supported. The dual network interface cards are built-in with 1GbE.

- Up to 36 channels 1080P/3M/4M/5M/8M/12M Network streaming
- Dual streaming decoding mode supported
- 1 monitor support up to 36 channels in total (480P 15fps)
- Support multi-channels synchronized playback (remote or local)
- Support Fisheye camera dewarping
- built-in 1 × 500GB 2.5 Inch SATA SSD (OS)
- Support up to 3 x 3.5 Inch SATA HDD (recording)
- Built-in 2 × 1GbE RJ-45
- Built-in 500W Power Supply
- 2U dimension for rackmount cabinet

Basic Spec	
Network video support	LILIN IP camera, LILIN IP camera over HTTPS, LILIN Fisheye camera, LILIN IP speed dome, LILIN DVR/ NVR, LILIN DHD recorder, NAV live streaming, P2P live streaming, ONVIF camera, manual RTSP, screen capture, USB video input, picture capture
Chassis	2U Chassis
Network video input	Up to 36 channels 1080P / 3M / 4M / 5M / 8M/12M
Network video format	H.264 / H.265 / MJPEG
Maximum network throughput	Upload: up to 500Mbps, Download: up to 500Mbps
Internal HDD / Swap Drive Bay	built-in 1 × 500GB 2.5 Inch SATA SSD (OS) Support up to 3 x 3.5 Inch SATA HDD (recording)
Video input	
Support quantity	Max. 36 channels
Camera name	20 characters
Channel editing	Mouse drag-n-drop
Fisheye Dewarp Mode	Ceiling and ground mounted, 1 R One Region, 3 R10 Three Regions One Fisheye, 4 R Four Regions, 2 R1P Two Regions One Panoramic 360, 2 P Two Panoramics 180, 8 R10 Eight Regions One Fisheye, Wall mounted, 1 R One Region, 3 R10 Three Regions One Fisheye, 4 R Four Regions, 2 R1P Two Regions One Panoramic 180, 1 WP One Wall Panoramic 180, 8 R10 Eight Regions One Fisheye
Digital zoom	Yes, ePTZ supported
Privacy Mask	Supported
Remote monitoring	Yes, web and NAV Client
Video output	
HDMI output	1 × HDMI Port 1.4b (4096 × 2160@24Hz)
VGA output	No support
DisplayPort output	1 × DisplayPort 1.2 (4096 × 2160@60Hz)
Split screen	4, 9, 16, 25, 36
Dual stream technology	Multi-channel displays D1 and full screen displays 1080P / 3M / 4M / 5M / 8M / 12M resolution
Multi-screen	1 monitor support up to 36 channels (480P 15FPS)
Recording mode	
Recording mode	Alarm, motion, schedule, and manual
Recording schedule	7 days × 24 hrs time table, recording mode configurable
Recording resolution & framerate	Max 12MP@20fps, 8MP@30fps, 5MP@30fps, 4MP@30fps, 3MP@30fps, 1080p@120fps, and ROI recording supported
Motion recording	N/A
Alarm recording	Remote digital input, remote IVS detection, remote face detection, remote tamper detection, remote audio detection, external IO, motion detection, NAV CGI Triggering, video loss detection, speed measurement detection, ANPR detection, facial recognition, remote LPR detection, QR code detection, aida behavior detection
Audio recording	Yes
Circular recording	Yes / size customizable
Limited recording	Yes / days customizable
Failover	Supported
Video archiving	Yes
Low bitrate recording	Yes
Remote network NAS	Support NAS (SMB/CIFS), iSCSI
Playback	
Playback search	Date, time, Smart search, Alarm search, POS, ANPR search, Face search, Face trace search (in FR server only), Tagging search
Playback resolution and framerate	Max 12MP@20fps, 8MP@30fps, 5MP@30fps, 4MP@30fps, 3MP@30fps, 1080p@120fps
Playback speed	Fast Rewind: 1/8, 1/4, 1/2, 1X, 2X, 4X, 8X, 16X, 32X Fast Forward: 1/8, 1/4, 1/2, 1X, 2X, 4X, 8X, 16X, 32X
Backup / Video input	Max. 36 channels, AVI & MP4 file format supported NAV Server / Navigator Client / DVR / NVR / IP camera
Remote video	SD card, maximum can support up to 36 channels playback and backup
Alarm / event	
Alarm management	Play audio file, send email notification, PTZ preset, digital output triggering, full screen, post alarm record, pre-alarm record, advanced alarm digital output, send customizable HTTP POST CGI URL to third party device, alarm ACK, alarm snapshot, text overlay, App cloud push notification, NCC TV wall ACK, NCC eMap Center Alarm, NCC play sound, NCC global alarm setting, all these action can be automatic or scheduled
Alarm recording	Pre-alarm:1 ~ 10 seconds and post-alarm: 1 sec ~ 59 minutes
Alarm Scheduling	Up to four alarm tables with AND logic
Alarm event actions	Various alarm log including video loss, stop recording, schedule, logon, operation log
Digital output	Controllable via IP cameras
Video archiving	
Video archiving & sync	Individual camera configurable, scheduling and instant archiving, sync recording data with NAV server / NVR / DVR / IP camera SD card.

Accessories	
Keyboard	PIH-931D keyboard controllable via rs-485 to usb converter for PTZ, ePTZ, and ROI features
Audio	PCM/G.711/AAC, two-way audio, audio recording
POS	Third party TCP/IP/ RS-232 / Bluetooth supported / HID USB Barcode scanner
Protocols	ARP / TCP/IP / RTSP / ONVIF / HTTP / HTTPS / SMTP / DNS / PPPoE / SDDP
Mobile support	LILIN Pror&Home, iPhone and Android
IP Scan	Supported, easy-to-setup for IP address
VMS support	Support NAV Client software
eMap	Supported
eMap Live Monitoring	Each map can see 9 live video at the same time
Auto Switch to the Map of Alarm Event	Supported
eMap Alarm Snapshot	Motion detection / external alarm / audio detection alarm / face detection
Alarm Event Actions	Digital output controllable, snapshots, and alarm popup
(eMap)Central Management	Centralized monitoring channels from multiple server
(eMap)Online Maps	Google map and Baidu map up to 128 eMap, GPS devices supported
Number of Mark for Online Map	Each online map can support 5000 camera mark
Number of Mark for Offline Map	Each offline map can support 500 camera mark
Hardware	
CPU	Intel® Core™ i5-10500
RAM	32GB (2 × DDR4 16GB)
Chipset	Intel® H410
Display card	Intel® UHD Graphics 630
Ethernet Ports	"1 x Intel® I219V with 1GbE 1 x Intel® I210 with 1GbE"
Audio	2 × Audio jack(s)
Rear panel USB port	2 × USB 3.1 Gen1 Type-A, 2 × USB 2.0 Type-A
Front panel USB port	1 × USB 3.0 Type-A
System fan	1 × 60mm rear exhaust fans
Hot spare	Not supported
SSD / HDD	"built-in 1 × 500GB 2.5 Inch SATA SSD (OS) Support up to 3 x 3.5 Inch SATA HDD (recording) Note: Do not use WD Purple HDDs for NAV HDD installation. Please use 7200RPM WD Red Pro for non-RAID installation, WD (Gold) Enterprise HDDs for RAID installation, or other Enterprise HDDs"
Other	
Language	English, Traditional Chinese, Spanish, German, French, Russian, Japanese, Portuguese, Italian, Simplified Chinese, Slovenian, Czech, Hungarian, Turkish, Arabic, Persian, Bengali, Vietnamese, Polish
OS	Windows 10 embedded SAC 21H2
DST	Daylight saving time by Windows OS
Warranty	3 years
Power and environment	
Power consumption	500W
Power supply	110V ~ 240V
Operating Temperature	0° C ~ 50° C (32° F ~ 122° F)
Storage Temperature	-20° C ~ 70° C (-4° F ~ 158° F)
Relative Humidity	10% ~ 90% (non-condensing)
Dimension (mm)	88 (H) × 438 (W) × 451 (D) mm
Color	Black
Weight	20.94 lbs (9.50kg) - Net