



---

## 16 CH 5Mega 19



---

## Features

- 16 Channel network camera Input
- Up to 5mega pixel H.264 network camera support
- Up to 1080P 60 FPS network camera support
- Internal HDD up to 8TB supported
- 19"2U Rack mount
- External e-SATA storage supported
- HDMI and VGA output up to 1920×1080P
- HDMI / VGA main or spot monitor switch
- Mobile phone ( iOS, Android ) solutions provided
- Network maximum input through up to 96Mbps
- Chrome, Edge, Firefox, IE, Opera, Safari supported
- Ethernet failure redundancy or sharing supported
- Dual redundant power supply supported

Discontinued date

- 2021.01.31

Alternative models

- NVR5416 or NVR5416E

---

## Description

LILIN NVR3816 is a 16-channel NVR (Network Video Recorder) designed for various recording applications. The system is equipped with an ARM Cortex A9 Dual-core processor with maximum recording throughput at 144 Mbps, and with two external eSATA connector ports for additional expansion up to 32TB. Setup of parameters such as IP address and basic IP camera configuration can easily be performed with LILIN setup wizard – IPScan and WS-Discovery, making the NVR3816 the easiest NVR system to use. With local VGA and HDMI display (with Full HD resolution at 1,920 x 1,080) and mouse and keyboard input available, configuring LILIN NVR is simple – an answer to meet most SMB owners' security needs.

---

## Specifications

Model	NVR3816
Supports (Video Input)/Network video /IP video	Network camera / ONVIF Profile S / DVR / NVR / Video encoder / Navigator
Input(IP video input)	16 CH
Resolution( IP video input )	CIF / VGA / D1 / 960H / 1M / 1.3M / 1080P / 3M / 5M
Maximum Frame Rate ( IP video input )	480 FPS
CE	Yes
FCC	Yes
Output (Video output)	HDMI / VGA 1080P, CVBS
Spot monitor (Video Display)	HDMI or VGA selectable ( Spot or sync. )
Split Screen	1 / 4 / 8 / 9 / 13 / 16 split division, sequence mode, freeze
Digital zoom	Up to 64× on live and playback
Network video Format	H.264
Maximum Network Throughput	96Mbps
Recording Resolution	CIF ~ 5M
Maximum Frame Rate	Single channel up to 1080P 60 FPS

Application/ Recording Mode	Manual, schedule ( continue, event, none )
Recording schedule	Each channel 7day × 24 hours time table, recording mode configurable
Alarm event actions	Motion grid (20×12, multi-level sensitivities) / network camera event / DI
Metadata options	POS RFID AND PIN CONTROLLER USER DEFINED 2 BARCODE SCANNER GPS LPR (Denial, Allowed, Visitor)
Alarm Notification (Recording)	Alarm notification iOS□android / E-Mail / FTP / buzzer / DO
Playback Search	Alarm event / Operation event / System event / Meta data event / Time search
Playback Display	16CH synchronous playback
Playback Resolution	CIF ~ 5M
Max. frame rate (Playback)	Up to 1080P 60FPS
Playback Speed	Fast rewind 2× ~ 64× / Fast forward 2× ~ 64× / Slow motion 1/2 ~ 1/16
Internal HDD / Swap Drive Bay	8 × 3.5" HDD (Up to 8TB supported)
eSATA	eSATA connector × 2 (Up to 32TB external storage supported, each 16TB)
USB Flash Disk(Backup)	Up to 32 GB supported
Network Backup	Via HTTP / FTP / Network Places
DVD DVD/RW(Backup)	External USB DVD/RW
Audio Input	16 CH (Network camera), G.711 u-law 8K & AAC
Audio Output	RCA × 1 (0.7Vp-p, 300 Hz to 3KHz)
Mic. input	RCA × 1
Line output	RCA × 1

Network Camera Two Way Audio / IP camera 2-way audio	Yes
Network ports	RJ-45 Gigabit Ethernet × 2 (Ethernet failure redundancy or sharing supported)
Protocols	ARP / TCP/IP / UDP / HTTP / HTTPS / SMTP / SNMP / FTP / DDNS / PPPoE / NTP / RTP / RTSP / DHCP/ Onvif Profile S
Web (Network)	Direct internet browser access / Multiple users access
Mobile Application	iOS / Android supported
P2P(Network)	APP scan QR Code / UID connection
RTSP service	RTP UDP/ RTSP TCP supported
IPScan / WS-Discovery( Network )	WS-Discovery and IP Scan, automatically quick IP address setup for network cameras
Network	Live / playback / backup / menu configuration / event log
VMS support	Navigator
Backup / Playback (Software)	Remote Playback Manager / Backup, multiple NVRs file download and multi-channel playback
Ports(Alarm)	DI × 16 and DO × 4 ( With programmable condition )
Reports( System )	Alarm event, operation, configuration and system execution log full reports exporting over HTTP or USB
Authentication ( System )	User authentication with feature configurable and IP address blocking
Languages	Arabic, Chinese( Traditional ), Chinese( Simplified ), English, French, German, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Turkish
HDD Inspection(System)	S.M.A.R.T monitoring / File system de-fragmentation/ IO read write error
Recording day	Automatic recording day calculator

Time	Daylight saving / NTP / External USB GPS time sync / Keyboard
PTZ protocol	Network HTTP / ONVIF, RS-485 × 1, MLP1 □ MLP2 □ PELCO D □ PELCO P
Keyboard Keypad	PIH-931D keyboard input
12V Output	12V / 1A output × 1
USB to RS-232	Record external metadata via USB to RS-232 cable, display at live and playback
RS-232	RS-232 Port × 1, record external metadata
Remote Controller	Remote controller addressable up to 255 NVRs (Optional)
Mouse	Mouse click, drag and scroll
Microphone	USB Mic (Optional)
Wi-Fi Dongle	WiFi and 4G external USB dongle supported (Certified brand only)
USB GPS Receiver	Support
CPU	ARM Cortex A9 Dual Core
OS	Embedded Linux Kernel 3.0
WDT	Hardware watchdog timer
Power Supply	Dual redundant power supply, Adapter DC 12V, 10A, 120W × 2, ((Optional))
Operating temperature	0°C ~ 45°C
Operating humidity	5% ~ 80%
Dimensions	438 × 450 × 88 mm
Weight	≈7 KG (Without hard drive)