



NAV 25CH Recorder



Features

- LILIN IP cameras, PTZ domes, and DVRs/NVRs are supported.
- Up to 25 channels 1080P/3M/5M/8M Network streaming, recording, and display.
- Tower chassis, Compact size, built-in software RAID system, support up to 4 x 3.5" HDD hot swap trays.
- Dual streamings decoding mode supported.
- Single Screen support, up to 25 channels Video display.
- Achieving management and record file sync.
- Support multi-channels playback/record file backup for remote or local.
- Built-in Gigabit Ethernet port.

Discontinued date

- 2018.10.13

Alternative models

- NAV2036A

Description

LILIN NAV 3025 25-channel recorder supports LILIN IP cameras, PTZ domes, and DVRs/NVRs. Up to 25 channels 1080P/3M/5M/8M network streaming, recording, and display. Tower chassis, Compact size, built-in software RAID system, support up to 4 x 3.5" HDD hot swap trays. video achieve, and SmartSearch support. Dual streaming decoding mode supported.

Single Screen support, up to 25 channels video display. Support multi-channels playback for remote or local. Built-in Gigabit Ethernet. Recording resolutions are 3,840 x 2,160, 2592 x 1944, 2048 x 1536, 1920 x 1080, 1280 x 1024, etc. NAV 3025 supports audio recording, circular recording, limited recording, video archiving, low bitrate recording, and remote network RAID.
