



1080P Day & Night Vari-Focal IR IP Dome Camera



Features

- Full HD 2 megapixel CMOS image sensor
- True H.264 AVC/MPEG-4 part 10
- H.264 and Motion JPEG triple video streaming
- 3D noise reduction (MCTF)
- 2D WDR function
- Digital zoom supported
- Audio / Motion detection alarm function
- Ceiling mount and Embedded mount installation
- High efficiency IR LED, radiant distance up to 25m
- Day & Night (IR cut removable)
- 2-way audio supported
- Digital I/O : 1 in, 1 out
- ONVIF supported

Discontinued date

- 2019.05.06

Alternative models

- M series / ZM series

-
- MR8322 / MR6422X
-

Description

Fixed dome LR2322EX in the L series is featuring embedded mount as well as ceiling mount installation in response to diverse array of environments for total situational awareness. The camera has built-in Sense Up+ technology to deliver stunning video in low-light conditions. Featuring high-efficiency IR-LEDs provide 25 meters of light. Utilizing intelligent image signal processing, 2D WDR function, AGC control, and 3D noise reduction, the combination successfully delivers the ultimate low-light image without motion blur. Support with PoE, privacy mask, white balance, and minimum illumination 0.05 Lux at F1.4 Low Light Mode.

With built-in IR-cut filter, white balance, back light compensation, and IVS features such as audio and motion detection to deliver quality videos.
